DIY RFC2136 dyndns with bind

ever since dyndns stopped to be completely free (including hassle-free) i was looking for alternatives. i recently stumbled across RFC2136 which can be used to provide dynamic dns services. since i have access to two nameservers running bind i decided to try it out.. it works pretty nicely:)

this is an improved version, now that i know more about bind, over my previous setup and it has been updated to work with bind 9.16 which no longer creates TSIG keys using dnssec-keygen but instead uses the much more comfortable tool tsig-keygen. The main disadvantage of my previous setup was, that any user holding one of the allowed keys could update any host entry, so the user was not limited to a single hostname which can be a seurity issue.

this following howto will explain how i did my setup so that i could have a little bash script that would allow me to add new hosts to my dyndns with a single command. all my hosts will end with .dyn.mydomain.ch.

i can run

```
/etc/bind/dyn/add_new_host.sh myhost
```

and it will add a new host called myhost.dyn.mydomain.ch to the configuration and return an authorization key which i can use on the client side.

so here is how i did it:

first of all i wanted to be able to have a simple script that would allow me to add new hosts with a minimum amount of work. so i split my config into different files, so i could later edit them automatically. also, you want to make sure the file where the keys are stored is not world readable..

create a directory that holds all the dynamic dns stuff:

```
mkdir /etc/bind/dyn
cd /etc/bind/dyn
```

create a basic zonefile for the dynamic dns zone. Important, you should use a dedicated subdomain with its own zone file for the dyndns stuff, as the zone file will be rewritten by bind later on and after that it is an absolute mess. so make sure you don't do this with your main zone file for your main domain! save the file as db.dyn.mydomain.ch in your dyn directory. here are the contents:

```
NS ns1.mydomain.ch.
NS ns3.mydomain.ch.
```

create an empty keys.conf file

```
touch keys.conf
```

create a file named.conf with the following contents

```
include "/etc/bind/dyn/keys.conf";

zone "dyn.mydomain.ch" {
   type master;
   file "/etc/bind/dyn/dyn.mydomain.ch";
   update-policy {
      grant *.dyn.mydomain.ch. self *.dyn.mydomain.ch. A;
      grant local-ddns zonesub any;
   };
   allow-query {
      ANY;
   };
};
```

• here are the contents of the script to add new hosts:

add new host.sh

```
#!/bin/bash
if [ -z "$1" -o "$1" == " " ]; then
       echo "usage: add new host.sh <hostname>"
       echo "EXAMPLE: add new host.sh myhost will add
myhost.dyn.mydomain.ch"
       exit 1
fi
cd /etc/bind/dyn/
hostname=${1}.dyn.mydomain.ch.
echo "generating key for ${hostname}"
key=$(tsig-keygen -a hmac-md5 ${hostname})
echo "here is the HMAC-MD5 key i have generated, use this to
configure your client:"
echo "-----"
echo "${key}" | grep "secret" | awk -F '"' '{print $2}'
echo "-----"
echo "add key to bind config"
echo $(echo "$key" | tr -d "\r\n") >> keys.conf
echo "reload bind";
/usr/sbin/rndc reload
echo "currently active hosts:"
grep "key " keys.conf | awk '{ print $2; }' | tr -d ";"
```

http://wiki.psuter.ch/ Printed on 06.11.2025 11:07

• now set the permissions so that especially the keys.conf file is only readable by bind and editable by root. also the dyn directory must be writeable by bind or if you don't want that, touch a file called dyn.mydomain.ch.jnl and make it writeable for bind, as well as making the dyn.mydomain.ch file writeable for bind. here is how i've set the permissions on my server:

```
drwxrwxr-- 2 root bind 4096 Oct 29 13:45 ./
drwxr-sr-x 3 root bind 4096 Oct 29 11:47 ../
-rwx----- 1 root root 904 Oct 29 13:45 add_new_host.sh*
-rw-r--r-- 1 bind bind 434 Oct 29 13:20 dyn.mydomain.ch
-rw-r--r-- 1 bind bind 1230 Oct 29 13:15 dyn.mydomain.ch.jnl
-rw-r---- 1 root bind 356 Oct 29 13:45 keys.conf
-rw-r--r-- 1 root bind 322 Oct 29 13:45 named.conf
```

• now use the script to add your first hostname.

```
./add_new_host myhost
```

if you did everything correctly (and if i described it all correctly) your client should now be able to update it's own dns entry with the key you received back from the script.

script to remove hosts

optionally you can also create a little script to remove hosts just as easily. create a file called remove_hosts.sh with the following contents

remove_hosts.sh

```
#!/bin/bash
if [ -z "$1" -o "$1" == " " ]; then
        echo "usage: remove host.sh <hostname>"
        echo "EXAMPLE: remove host.sh myhost will remove
myhost.dyn.mydomain.ch"
        exit 1
fi
cd /etc/bind/dyn/
hostname=${1}.dyn.mydomain.ch.
echo "old keys.conf entry: "
grep -E '[ "]'"${hostname}"'[."]\s' keys.conf
echo "remove key for ${hostname}"
sed -i '/[ "]'"${hostname}"'[."]\s/d' keys.conf
echo "reload bind";
/usr/sbin/rndc reload
echo "delete dns entry for ${hostname}"
echo -e "update delete ${hostname} a\nsend" | nsupdate -l -4
/usr/sbin/rndc sync -clean
echo "currently allowed hosts:"
grep "key " keys.conf | awk '{ print $2; }' | tr -d ";"
```

make it executable and run it to remove hotsts. **warning** make a backup of your keys.conf and your named.conf file before testing this:)

./remove_host.sh myhost

From:

http://wiki.psuter.ch/ - pswiki

Permanent link:

http://wiki.psuter.ch/doku.php?id=diy_rfc2136_dyndns_with_bind





http://wiki.psuter.ch/ Printed on 06.11.2025 11:07